

SATELLITE MODEM: A3LA-R

Key Features

- Low-cost
- Small form-factor
- Capable of SBD, SMS, data switch, RUDICS and voice
- RS-232 interface
- Functionally is the same as the 9522B
- ~60% smaller in volume than the 9522B
- ~50% lighter than the 9522B
- A3LA-R-MIL is certified to MIL-STD-810G standards and IP67 rating

Description

The A3LA-R is a satellite modem comprised of an Iridium 9523 transceiver. It allows SBD, SMS, data switch and RUDICS connectivity to the Iridium satellite network. With a connected DPL handset, the A3LA-R can place voice calls similar to an Iridium 9555/9575 phones.

Options

A3LA-RG/RGS is an A3LA-RM with internal GPS receiver and tracking capability.



A3LA-R Specifications

Mechanical

Dimensions:	4.0" x 2.43" x 0.95" (102 mm x 61 mm x 24 mm)
Weight:	7.0 ounces (198 g)
Data/Power Interface:	25-Pin D-Sub
Antenna Interface:	TNC female connector
Enclosure:	Hard-anodized aluminum (EMI/EMC shielded)

Electrical

Input Voltage Range:	4.0V to 5.5V or 5.0V to 32V
Nominal Input:	5VDC
Idle Power:	80mA @ 5V
Transmitted Power:	350mA @ 5V

RF Boards

Iridium Transceiver:	Iridium 9523
----------------------	--------------

Environmental

Operating Temperature:	-22°F to +158°F (-30°C to +70°C)
Operating Humidity:	< 75% RH



POWERED by the **IRIDIUM NETWORK**



9385 Discovery Boulevard Suite 300, Manassas, VA 20109 www.nalresearch.com